

The New Leading Role!

Curtain up for Hannoband®-3E Easy – the new top multi-functional tape from the inventor of the moisture-variable membrane technology. With external membranes to protect the functional layer.



Advantages at a glance

- Flexible use: suitable to meet all MF1 and MF2 specifications
- Easy handling due to neutral running direction (each side of the tape may face the interior respectively exterior)
- Moisture-variable for permanently dry connection joints
- Airtight and driving rain-tight up to 1050 Pa (21.93 Psf)
- UV and weather resistant
- Assessed joint noise reduction $R_{s,w}$ 57 dB (not plastered)
- Suitable for passive houses and new building constructions
- MPA-tested and GEG-compliant (German Building Energy Act)

More information: see back cover



Multi-Functional Tape

Hannoband®-3E Easy

The new multi-functional tape with external HANNO high-performance membranes ensures permanently dry connection joints.

Hannoband®-3E Easy has been tested by MPA BAU HANNOVER and has been proven to be moisture-variable. The pre-compressed and impregnated multi-functional sealing tape is based on soft polyurethane foam. The incorporated acrylate dispersion impregnation provides the required product performance with numerous properties.

Hannoband®-3E Easy is airtight on the interior, sound and thermal insulating in the center and driving rain-tight on the exterior. The moisture-variable functional membranes adjust their water vapor permeability to the moisture load. In this way, moisture can be transported out and the joint can dry out all year round.

Depending on the compression rate, the product can be flexibly used and meets MF1 as well as MF2 requirements.

Roll format with acrylate adhesive as installation aid. For professional sealing of all functional areas in window joints with only one product.



Quick and easy installation at any time of the year



Product overview

Tape width (mm)*	Area of application		Roll length (m)
	Concealed installation (MF2)	Directly weather exposed (MF1)	
56	5-15 9-22 12-30 18-40	5-13 9-18 12-25 18-35	14.1 9.4 7 4.7
64	5-15 9-22 12-30 18-40	5-13 9-18 12-25 18-35	14.1 9.4 7 4.7
74	5-15 9-22 12-30 18-40	5-13 9-18 12-25 18-35	14.1 9.4 7 4.7
84	5-15 9-22 12-30 18-40	5-13 9-18 12-25 18-35	14.1 9.4 7 4.7

Hanno Werk GmbH & Co. KG

Hanno-Ring 3-5
30880 Laatzen
Germany

Phone: +49 5102 7000-0
info@hanno.com
www.hanno.com

